

LICO GRUNT UNIWERSALNY

priming emulsion



Instructions of Use

Lico Grunt UNIWERSALNY is used in not diluted form, applying evenly thin layer on the surface with a brush, paint roller or spraying. On very absorbent surfaces repeat grounding before the first layer completely dries.

Surface temperature should be from +5°C to +30°C. Emulsion drying time on surface: max 3 hours.

Use on surfaces exposed to temperature fluctuations from -20°C to +80°C.

Product Characteristics

This deep-penetrating emulsion is a modern agent used for priming all substrates exhibiting high absorptiveness and porosity. It is used with concrete, gas concrete, cement, cement-lime, bricked, gypsum, drywall etc. substrates. Applied before laying putties, gypsums, paints, glues, plasters, joints and compensating coatings. The preparation reinforces even very weak and brittle surfaces thanks to its large penetrability, providing adequate strength and resistance to humidity. It increases adhesion of glue to glaze and terracota, preventing the formation of air bubbles beneath self-leveling floorings; reduces consumption of paints. For indoor and outdoor use. The emulsion is not intended for smooth concrete surfaces and beneath silicate paints.

Recommendations

Emulsion must be stored in rooms not exposed to direct sunlight, in tightly closed containers, protected against freezing; **at the temperature above +5°C**. Shelf life of emulsion in original closed manufacturer's packing is 12 months.

Notes

Manufacturer has no control over incorrect use of material, its application for other purposes or in other conditions than specified. In case of any doubt, make your own test or consult manufacturer. Manufacturer shall not be liable for any use of product not in compliance with instructions on the packaging.

Technical Data

Average consumption:	~ 0,1 l/m ²
Drying time:	max 3 hours
Ambient and surface temperature:	from +5°C to +30°C
Shelf life:	12 months
Storage temperature:	> +5°C
VOC content acc. to Directive 2004/42/EC cat. A/g,h/WB:	as of 01.01.2010 - 30 g/l.
Maximal VOC content in ready-to-use product:	30 g/l
Contains: 1,2-benzoizothiazol-3(2H)-on, 2-methyl-2H-isothiazol-3-on, mixture 5-chloro-2-methylo-2H-isothiazol-3-onu and 2-methylo-2H-isothiazol-3-onu (3:1). May produce an allergic reaction.	
P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P 264 Carefully wash hands after use.	
Packaging:	1, 5, 10 liters
Pallets, respectively:	360, 108, 60 pcs.
*depending on surface type and absorptiveness, ambient temperature.	

LICO MIX®

LICO MIX sp. z o.o.
Al. Jana Pawła II 4, 38-404 Krosno, Poland
Tel. : +48 16 624 11 80, Fax : +48 16 624 11 82
biuro@lico-mix.pl www.lico-mix.pl